

# ACOSFLOR

flooring selection

It is a heterogeneous LVT floor that combines a large wear resistance with a long service life, aesthetic sophistication and countless advantages for use in the most diverse spaces. Anti-allergic spaces, very good thermal quality, excellent wear resistance, withstand the heaviest loads, a product with the most stable dimensions, resistance in humid environments, excellent surface treatment, easy installation and maintenance.

## THERMOFIX ART

### Technical Data

Declaration of performance	EN 14041:2004	544420021
Total thickness	EN ISO 24346	2,2 mm
Wear layer thickness	EN ISO 24340	0,6 mm
Tile size	EN ISO 24342	1829x180 mm
Plank size	EN ISO 24342	max. 0,25 mm
Total weight	EN ISO 23997	3200 gr/m <sup>2</sup>
Area of application	EN ISO 10581,10582	33/42
Residual indentation	EN ISO 24343-1	max. 0,1 mm
Dimensional stability	EN ISO 23999	max. 0,25%
color fastness	EN ISO 105-B02	Grade 6
Wear hardness	EN 660-2	NPD
flammability	EN 13501-1	Bfl-s1
Anti-slipping	DIN 51130	R 11
	EN 14041	DS
Thermal conductivity	EN 14041	0,17 W/(m.k)
floor heating		Suitable
Resistance to microorganisms	EN ISO 846	Yes
Resistance to stains	EN ISO 26987	Yes
Flexibility	EN ISO 24344	Ø20 mm
Formaldehyde emission	EN 14041	E1(no emission)
Castor chair resistance	EN 425	Yes
phtalate free production		Yes
Warranty		10 years

